



Features:

- No UV or IR light radiation.
- Provide 140° beam angles.
- Easy Installation.
- Low Power Consumption: Less than 60 Watts.
- Long lifetime: 25000 hours (L₇₀).
- Sturdy Construction:
- UV Stabilized toughened glass and Aluminum alloy Lamp Base.
- High CRI: 70-85
- Correlated Color Temperature: 2700-6500K.
- Operating temperature: -20°C~+60°C.
- 90-265V AC input.
- Protection grade: IP65.

Benefits:

- Energy Cost Savings:
Over 60% Compared to Incandescent.
- Solid-State:
High-Shock & High-Vibration Resistant,
Both Electrical and Mechanical
- Energy Cost Savings:
- Eco-Friendly:
No Mercury, No Lead Content
- No Hazardous Emissions:
No UV or IR Radiation
- Constant Light Output:
Even Lighting, Non-Halation

Applications:


- Street /Parking lot lighting.
- park, sculpture and national green lighting project
- Tourist attractions lighting
- Green area lighting.
- The building elevation of lighting
- Other Lighting

Product Specifications:

Diffuser	PMMA
Input Voltage	90-265V AC
IP	IP65
Wattage	60W
Power Factor	PF \geq 0.8
Operating frequency	50-60Hz
Operating Temperature	-20°C ~ +60°C
Storage Temperature	-30°C ~ +60°C
Net Weight per piece (Kg)	4KG
Certifications	RoHS Compliant

Product Selection Guide:

Part No.	Beam Angle	Total Lumens	CCT	Color	CRI
SL-WW60WC	140°	5900±5%	2700-3500K	Warm White	\geq 70
SL-W60WC	140°	6000±5%	5500-6500K	White	\geq 70



LED Street Light Lamp Series




Data Sheet

SL-XX60WC

AC90-265V, 60W

①	SL:	Product Type.
②	XX:	WW-Warm White W-White
③	60W:	The single LED power is 60W
④	C:	AC90-265V



Product Dimensions:



Notes:

1. All dimensions unit in mm
2. Tolerances are $\pm 0.5\text{mm}$ unless otherwise noted.

Package Dimension:



Small carton
630L*270W*110Hmm
(24.81"L*10.63"W*4.33"H)
1pcs Street Light inside

Installation Instructions and Warnings:

- Turn off power before inspection, installation, or removal.
- Not for use where exposed to the weather
- Do not use in totally enclosed fixtures.
- Not for use with dimmers.
- Please make sure to use a suitable adapter. Please mind the minimum load of your adapter.

Notes:

The part number, type, and specifications mentioned in this document are subject to future change and improvement without notice. Before production usage customer should refer to the latest datasheet for the updated specifications.